



ISO 측정항목

382P

단위 Unit: mm

Order Number	피치규격날수산수		Flutes Z	Teeth Zt	날경 Diameter		유효장 Effective Length L2	길이 LkL	전장 Overall Length	샙크 Shank Dia d	
	Thread	Pitch			D0D2	D1					
외부급유형 (Without coolant)											
4ETM 024 070 S06 M3	M3	0.5	4	2	1.37	2.17	2.4	7	0.4	60	6
4ETM 024 085 S06 M3	M3	0.5	4	2	1.37	2.17	2.4	8.5	0.4	60	6
4ETM 032 092 S06 M4	M4	0.7	4	2	1.74	2.88	3.2	9.2	0.57	60	6
4ETM 032 112 S06 M4	M4	0.7	4	2	1.74	2.88	3.2	11.2	0.57	60	6
4ETM 039 115 S06 M5	M5	0.8	4	2	2.21	3.61	3.9	11.5	0.7	60	6
4ETM 039 144 S06 M5	M5	0.8	4	2	2.21	3.61	3.9	14.4	0.7	60	6
4ETM 047 140 S06 M6	M6 ~ M9	1	4	2	2.82	4.4	4.7	14	0.79	60	6
4ETM 047 170 S06 M6	M6 ~ M9	1	4	2	2.82	4.4	4.7	17	0.79	60	6
4ETM 061 180 S08 M8	M8 ~ M12	1.25	4	2	4	5.8	6.1	18	0.9	65	8
4ETM 061 220 S08 M8	M8 ~ M12	1.25	4	2	4	5.8	6.1	22	0.9	65	8
4ETM 078 230 S08 M10	M10 ~ M15	1.5	4	2	5.16	7.4	7.8	23	1.12	65	8
4ETM 078 280 S08 M10	M10 ~ M15	1.5	4	2	5.16	7.4	7.8	28	1.12	65	8
4ETM 090 260 S10 M12	M12	1.75	4	2	6.2	8.6	9	26	1.2	80	10
4ETM 090 330 S10 M12	M12	1.75	4	2	6.2	8.6	9	33	1.2	80	10
4ETM 118 350 S12 M16	M16 ~ M23	2	4	2	7.4	11.4	11.8	35	2	100	12
4ETM 118 430 S12 M16	M16 ~ M23	2	4	2	7.4	11.4	11.8	43	2	100	12

내부급유형 (With coolant)

4ETM 047 140 S06 M6C	M6 ~ M9	1	4	2	2.82	4.4	4.7	14	0.79	60	6
4ETM 047 170 S06 M6C	M6 ~ M9	1	4	2	2.82	4.4	4.7	17	0.79	60	6
4ETM 061 180 S08 M8C	M8 ~ M12	1.25	4	2	4	5.8	6.1	18	0.9	65	8
4ETM 061 220 S08 M8C	M8 ~ M12	1.25	4	2	4	5.8	6.1	22	0.9	65	8
4ETM 078 230 S08 M10C	M10 ~ M15	1.5	4	2	5.16	7.4	7.8	23	1.12	65	8
4ETM 078 280 S08 M10C	M10 ~ M15	1.5	4	2	5.16	7.4	7.8	28	1.12	65	8
4ETM 090 260 S10 M12C	M12	1.75	4	2	6.2	8.6	9	26	1.2	80	10
4ETM 090 330 S10 M12C	M12	1.75	4	2	6.2	8.6	9	33	1.2	80	10
4ETM 118 350 S12 M16C	M16 ~ M23	2	4	2	7.4	11.4	11.8	35	2	100	12
4ETM 118 430 S12 M16C	M16 ~ M23	2	4	2	7.4	11.4	11.8	43	2	100	12

Inch 측정항목

단위 Unit: mm

Order Number	피치규격		날수 Flutes Z	산수 Teeth Zt	날경 Diameter		유효장 Effective Length L2	길이 LkL	전장 Overall Length	생크 Shank Dia d	
	Thread	Pitch			D0D2	D1					
외부 급유형 (Without coolant)											
4ETM 021 072 S06	NO.4-40	40	4	2	1	1.76	2.1	7.2	0.38	60	6
4ETM 021 088 S06	NO.4-40	40	4	2	1	1.76	2.1	8.8	0.38	60	6
4ETM 026 086 S06	NO.6-32	32	4	2	1.32	2.21	2.6	8.6	0.45	60	6
4ETM 026 105 S06	NO.6-32	32	4	2	1.32	2.21	2.6	10.5	0.45	60	6
4ETM 030 100 S06	NO.8-32	32	4	2	1.42	2.62	3	10	0.6	60	6
4ETM 030 122 S06	NO.8-32	32	4	2	1.42	2.62	3	12.2	0.6	60	6
4ETM 035 114 S06	NO.10-24	24	4	2	1.58	3.18	3.5	11.4	0.8	60	6
4ETM 048 145 S06	1/4" x 20	20	4	2	2.69	4.29	4.8	14.5	0.8	60	6
4ETM 048 180 S06	1/4" x 20	20	4	2	2.69	4.29	4.8	18	0.8	60	6
4ETM 050 144 S06	1/4" x 28	28	4	2	3.2	4.58	5	14.4	0.69	60	6
4ETM 050 178 S06	1/4" x 28	28	4	2	3.2	4.58	5	17.8	0.69	60	6

내부 급유형 (With coolant)

4ETM 048 145 S08C	1/4" x 20	20	4	2	2.69	4.29	4.8	14.5	0.8	65	6
4ETM 048 180 S08C	1/4" x 20	20	4	2	2.69	4.29	4.8	18	0.8	65	6
4ETM 050 144 S08C	1/4" x 28	28	4	2	3.2	4.58	5	14.4	0.69	65	8
4ETM 050 178 S08C	1/4" x 28	28	4	2	3.2	4.58	5	17.8	0.69	65	8
4ETM 065 176 S08C	5/16"-24	24	4	2	4.34	6.02	6.5	17.6	0.85	65	8
4ETM 065 218 S08C	5/16"-24	24	4	2	4.34	6.02	6.5	21.8	0.85	65	8
4ETM 067 260 S08C	3/8"-16	16	4	2	3.98	6.18	6.7	26	1.1	65	8

4ETM Cutting Condition

피삭재 Material	합금강/ 공구강 Alloy Steel/ Tool Steel		고경도강 Hardened Steels		알루미늄 Aluminum		스테인레스강 Stainless Steel	
경도 Hardness	~ 30HRC		35 ~ 45HRC					
TAP	V/C	FZ	V/C	FZ	V/C	FZ	V/C	FZ
M3	50 ~ 70	0.01 ~ 0.02	45 ~ 55	0.005 ~ 0.01	100 ~ 130	0.03 ~ 0.04	70 ~ 80	0.015 ~ 0.025
M4	50 ~ 70	0.01 ~ 0.02	45 ~ 55	0.005 ~ 0.01	100 ~ 130	0.03 ~ 0.04	70 ~ 80	0.015 ~ 0.025
M5	50 ~ 70	0.01 ~ 0.02	45 ~ 55	0.005 ~ 0.01	100 ~ 130	0.03 ~ 0.04	70 ~ 80	0.015 ~ 0.025
M6	50 ~ 70	0.02 ~ 0.03	45 ~ 55	0.01 ~ 0.015	100 ~ 130	0.04 ~ 0.05	70 ~ 80	0.025 ~ 0.035
M8	50 ~ 70	0.02 ~ 0.03	45 ~ 55	0.01 ~ 0.015	100 ~ 130	0.04 ~ 0.05	70 ~ 80	0.03 ~ 0.04
M10	50 ~ 70	0.02 ~ 0.03	45 ~ 55	0.015 ~ 0.02	100 ~ 130	0.05 ~ 0.06	70 ~ 80	0.03 ~ 0.04
M12	50 ~ 70	0.03 ~ 0.04	45 ~ 55	0.02 ~ 0.025	100 ~ 130	0.06 ~ 0.07	70 ~ 80	0.03 ~ 0.04
M16	50 ~ 70	0.03 ~ 0.04	45 ~ 55	0.02 ~ 0.025	100 ~ 130	0.06 ~ 0.07	70 ~ 80	0.04 ~ 0.05

4MTM Cutting Condition

피삭재 Material	합금강/ 공구강 Alloy Steel/ Tool Steel		고경도강 Hardened Steels		알루미늄 Aluminum		스테인레스강 Stainless Steel	
경도 Hardness	~ 30HRC		35 ~ 45HRC					
TAP	V/C	FZ	V/C	FZ	V/C	FZ	V/C	FZ
M1	50 ~ 70	0.005 ~ 0.01	55 ~ 65	0.005 ~ 0.01	100 ~ 130	0.02 ~ 0.34	70 ~ 85	0.005 ~ 0.01
M2	50 ~ 70	0.005 ~ 0.01	55 ~ 65	0.005 ~ 0.01	100 ~ 130	0.02 ~ 0.34	70 ~ 85	0.005 ~ 0.01
M3	50 ~ 70	0.01 ~ 0.02	55 ~ 65	0.01 ~ 0.02	100 ~ 130	0.02 ~ 0.34	70 ~ 85	0.005 ~ 0.01
M4	50 ~ 70	0.01 ~ 0.02	55 ~ 65	0.01 ~ 0.02	100 ~ 130	0.04 ~ 0.05	70 ~ 85	0.01 ~ 0.02
M5	50 ~ 70	0.02 ~ 0.03	55 ~ 65	0.02 ~ 0.03	100 ~ 130	0.04 ~ 0.05	70 ~ 85	0.01 ~ 0.02
M6	50 ~ 70	0.02 ~ 0.03	55 ~ 65	0.02 ~ 0.03	100 ~ 130	0.05 ~ 0.06	70 ~ 85	0.02 ~ 0.03

4STM Cutting Condition

피삭재 Material	합금강/ 공구강 Alloy Steel/ Tool Steel		고경도강 Hardened Steels		알루미늄 Aluminum		스테인레스강 Stainless Steel	
경도 Hardness	~ 30HRC		35 ~ 45HRC					
TAP	V/C	FZ	V/C	FZ	V/C	FZ	V/C	FZ
M3	50 ~ 70	0.01 ~ 0.02	55 ~ 65	0.008 ~ 0.01	100 ~ 130	0.03 ~ 0.04	70 ~ 85	0.01 ~ 0.02
M4	50 ~ 70	0.01 ~ 0.02	55 ~ 65	0.008 ~ 0.01	100 ~ 130	0.03 ~ 0.04	70 ~ 85	0.01 ~ 0.02
M5	50 ~ 70	0.01 ~ 0.02	55 ~ 65	0.01 ~ 0.02	100 ~ 130	0.03 ~ 0.04	70 ~ 85	0.01 ~ 0.02
M6	50 ~ 70	0.01 ~ 0.02	55 ~ 65	0.01 ~ 0.02	100 ~ 130	0.04 ~ 0.05	70 ~ 85	0.02 ~ 0.03
M8	50 ~ 70	0.02 ~ 0.03	55 ~ 65	0.02 ~ 0.03	100 ~ 130	0.04 ~ 0.05	70 ~ 85	0.02 ~ 0.03
M10	50 ~ 70	0.02 ~ 0.03	55 ~ 65	0.02 ~ 0.03	100 ~ 130	0.05 ~ 0.06	70 ~ 85	0.03 ~ 0.04
M12	50 ~ 70	0.02 ~ 0.03	55 ~ 65	0.02 ~ 0.03	100 ~ 130	0.06 ~ 0.07	70 ~ 85	0.05 ~ 0.06
M16	50 ~ 70	0.03 ~ 0.04	55 ~ 65	0.03 ~ 0.04	100 ~ 130	0.06 ~ 0.07	70 ~ 85	0.05 ~ 0.06

4HTM Cutting Condition

피삭재 Material	합금강/ 공구강 Alloy Steel/ Tool Steel		고경도강 Hardened Steels		알루미늄 Aluminum		스테인레스강 Stainless Steel	
경도 Hardness	~ 30HRC		35 ~ 45HRC					
TAP	V/C	FZ	V/C	FZ	V/C	FZ	V/C	FZ
M3	50 ~ 70	0.01 ~ 0.02	50 ~ 60	0.005 ~ 0.008	100 ~ 130	0.03 ~ 0.04	70 ~ 85	0.01 ~ 0.02
M4	50 ~ 70	0.01 ~ 0.02	50 ~ 60	0.005 ~ 0.008	100 ~ 130	0.03 ~ 0.04	70 ~ 85	0.01 ~ 0.02
M5	50 ~ 70	0.01 ~ 0.02	50 ~ 60	0.01 ~ 0.02	100 ~ 130	0.03 ~ 0.04	70 ~ 85	0.01 ~ 0.02
M6	50 ~ 70	0.01 ~ 0.02	50 ~ 60	0.01 ~ 0.02	100 ~ 130	0.04 ~ 0.05	70 ~ 85	0.02 ~ 0.03
M8	50 ~ 70	0.02 ~ 0.03	50 ~ 60	0.02 ~ 0.03	100 ~ 130	0.04 ~ 0.05	70 ~ 85	0.02 ~ 0.03
M10	50 ~ 70	0.02 ~ 0.03	50 ~ 60	0.02 ~ 0.03	100 ~ 130	0.05 ~ 0.06	70 ~ 85	0.03 ~ 0.04
M12	50 ~ 70	0.02 ~ 0.03	50 ~ 60	0.02 ~ 0.03	100 ~ 130	0.06 ~ 0.07	70 ~ 85	0.05 ~ 0.06
M16	50 ~ 70	0.03 ~ 0.04	50 ~ 60	0.03 ~ 0.04	100 ~ 130	0.06 ~ 0.07	70 ~ 85	0.05 ~ 0.06

- 가급적 열박음 척을 추천합니다.
- 공구 진입시 이송 f (mm/tooth)를 나사가공 이송 대비 30% 수준으로 낮춰 주십시오.
- 상기 절삭조건은 참고 수치이므로, 실 가공시 가공 형상, 가공 목적, 적용 기계에 따라 조건변경 요망 합니다.
- 절삭시 내,외부 급유형 쿨런트 사용을 추천합니다.
- Using shrink-fit chuck is recommended.
- When the tool approaches the work material, reduce the feed by 30%.
- Use this table for your reference. Adjust the parameters depending on your machining geometry, machining purpose and CNC.
- Internal and external coolants are recommended for milling.

Your specials are our standards.

당신의 스페셜은 우리의 표준품입니다.

WWW.JJTOOLS.CO.KR

LONG Life HIGH Performance

FINISHING INSERTS

High-speed machining for long life. High quality cutting surface by high precision of insert. High speed cutting. High performance in high speed machining. High quality cutting surface by high precision of insert. High speed cutting. High performance in high speed machining.

LOW Price HIGH Performance

NEW FLAT DRILL

Applied flat design for inclined or curved surfaces when counter boring and drilling.

45TM 시리즈 20TM

THREAD MILLS

Drilling, threading and chamfering in one tool operation.

DENTAL SERIES

정밀 제조시용 CAD/CAM Milling Bit

강하고 오래가는 - 나노 다이아몬드 코팅!

흡착현상을 최소화!

For Composite Materials